1 4.12 NOISE

	Issues & Supporting Information Sources	Potentially Significant Impact	Less Than Significant With Mitigation Incorporated	Less Than Significant Impact	No Impact
Would the Project result in:					
a.	Exposure of persons to or generation of noise levels in excess of standards established in the local general plan or noise ordinance, or applicable standards of other agencies?			\boxtimes	
b.	Exposure of persons to or generation of excessive groundborne vibration or groundborne noise levels?				\boxtimes
C.	A substantial permanent increase in ambient noise levels in the project vicinity above levels existing without the project?			\boxtimes	
d.	A substantial temporary or periodic increase in ambient noise levels in the project vicinity above levels existing without the project?			\boxtimes	
e.	For a project located within an airport land use plan or, where such a plan has not been adopted, within two miles of a public airport or public use airport, would the project expose people residing or working in the project area to excessive noise levels?				\boxtimes
f.	For a project within the vicinity of a private air strip, would the project expose people residing or working in the project area to excessive noise levels?				\boxtimes

2

3 4.12.1 Environmental Setting

4 4.12.1.1 Fundamental Noise Principles

Noise may be defined as unwanted sound. Noise is usually objectionable because it is disturbing 5 or annoying. Several noise measurement scales are used to describe noise in a particular location. 6 A decibel (dB) is a unit of measurement that indicates the relative amplitude of a sound. The zero 7 on the decibel scale is based on the lowest sound level that the healthy, unimpaired human ear 8 9 can detect. Sound levels in decibels are calculated on a logarithmic basis. An increase of 10 dB represents a 10-fold increase in acoustic energy, while 20 dB is 100 times more intense, 30 dB is 10 1,000 times more intense, etc. There is a relationship between the subjective noisiness or 11 loudness of a sound and its intensity. Each 10-dB increase in sound level is perceived as 12 approximately a doubling of loudness over a fairly wide range of intensities. 13

There are several methods of characterizing sound. The most common is the A-weighted sound level, or dBA. This scale gives greater weight to the frequencies of sound to which the human ear is most sensitive. Because sound levels can vary markedly over a short period of time, a method for describing either the average character of the sound or the statistical behavior of the variations must be utilized. Most commonly, sounds are described in terms of an average level that has the same acoustical energy as the summation of all the time-varying events. This energyequivalent sound/noise descriptor is called L_{eq} . The most common averaging period is hourly, but L_{eq} can describe any series of noise events of arbitrary duration.

Because the sensitivity to noise increases during the evening and at night—excessive noise 3 interferes with the ability to sleep-24-hour descriptors have been developed that incorporate 4 5 artificial noise penalties added to quiet-time noise events. The Community Noise Equivalent Level (CNEL) is a measure of the cumulative noise exposure in a community, with a 5-dB 6 penalty added to evening (7:00 p.m. to 10:00 p.m.) and a 10-dB addition to nocturnal (10:00 p.m.) 7 8 to 7:00 a.m.) noise levels. The Day/Night Average Sound Level (L_{dn}) is essentially the same as 9 CNEL, with the exception that the evening time period is dropped and all occurrences during this 3-hour period are grouped into the daytime period. 10

11 **4.12.1.2 Existing Conditions**

The Project site is located in a remote rural area. Primary sources of noise are agricultural 12 activities on adjacent farmlands, although the use of power boats also would cause periodic noise 13 increases. The EPA has indicated that background noise levels are generally near 44 to 45 dBA 14 L_{dn} in agricultural cropland (EPA 1978). Some land uses are generally regarded as being more 15 sensitive to noise than others due to the types of population groups or activities involved. Single-16 or multiple-family residences, schools, hospitals, churches, and public libraries are typically 17 18 considered to be noise-sensitive receptors. The nearest known sensitive receptors are liveaboards at the marina located approximately 4,120 feet south of the Old River site. There are no noise-19 sensitive land uses near the Connection Slough site. 20

21 4.12.2 Regulatory Setting

Noise is regulated at the local level through policies and standards included in the Noise 22 Elements of the Contra Costa County (2005) and San Joaquin County (1992) General Plans. The 23 24 Contra Costa County (2005) General Plan specifies that noise levels in agricultural areas are normally acceptable up to 75 dBA (L_{dn} or CNEL) and conditionally acceptable up to 80 dBA. 25 Noise levels in residential areas are normally acceptable up to 60 dBA and conditionally 26 acceptable up to 70 dBA. Policy 11-9 states that: "Construction activities shall be concentrated 27 during the hours of the day that are not noise-sensitive for adjacent land uses and should be 28 commissioned to occur during normal work hours of the day to provide relative quiet during the 29 more sensitive evening and early morning periods." (Contra Costa County 2005) 30

31 The San Joaquin County (1992) General Plan Public Health and Safety Element, Section D, Noise, does not address construction noise, but indicates that the hourly equivalent sound level 32 from stationary noise sources shall be 50 dB during the daytime and 45 dB during the nighttime 33 for outdoor activity areas for residential development and that the maximum sound level from 34 stationary sources shall be 70 dB during the nighttime at such areas (San Joaquin County 1992). 35 The San Joaquin County Code, Part 9-1025.9 also contains noise standards. It exempts 36 37 construction noise from the provisions of the noise chapter, as long as construction activities do not take place before 6 a.m. or after 9 p.m. on any day. Maximum allowable noise exposure at 38 residential outdoor activity areas from stationary noise sources is 50 dB Lea from 7 a.m. to 10 39 p.m. and 45 dB Leq from 10 p.m. to 7 a.m. The maximum sound level (Lmax) during these periods 40 is 70 dB and 65 dB, respectively. 41

1 4.12.3 Impacts and Mitigation Measures

2 **4.12.3.1** No Project

3 The No Project alternative would not affect noise because no development would occur.

4 **4.12.3.2 2-Gates Project**

5 The Project would generate noise primarily through the installation and removal of Project 6 components. The construction equipment and activities are those identified in Section 4.3, Air 7 Quality; impacts from the removal of Project components would be similar to those from their 8 installation, but would occur for a shorter duration.

9 a. Exposure of persons to or generation of noise levels in excess of standards established in the 10 local general plan or noise ordinance, or applicable standards of other agencies

Less than Significant. Noise from a point source, such as a construction site, attenuates, or is reduced, by about 6 dBA for every doubling of the distance. Noise at the marina south of the Old River site would attenuate to 59 L_{dn} or CNEL, which is within the limits of what Contra Costa County considers acceptable in residential locations. Given the short-term nature of this impact, it is considered less than significant. *Note to reviewers: discussion of noise impacts from impact hammers to be added.*

There are no residential outdoor activity areas near the Connection Slough site, and the Project would not create stationary noise sources at this site; therefore, Project construction would not expose persons to or generate noise levels in excess of established San Joaquin County noise standards.

b. Exposure of persons to or generation of excessive groundborne vibration or groundborne noise levels

23 **No Impact.** The primary source of vibration would be vibration pile driving in the channels during construction. The vibration pile driver typically results in an approximate vibration 24 velocity level (velocity in decibels or VdB) of approximately 93 VdB at 25 feet (FTA 2006). 25 Vibration attenuates very rapidly, and there are no sensitive receptors in the immediate vicinity 26 27 of the Project sites. The nearest receptors are live-aboard residents at the marina located approximately 4,120 feet from the Old River site, and they would not experience groundborne 28 29 vibration or noise. Note to reviewers: discussion of noise impacts from impact hammers to be added. 30

31 c. A substantial permanent increase in ambient noise levels in the project vicinity above levels 32 existing without the project

Less than Significant The Project would not create permanent noise sources. Two small generators could be operated intermittently at the Old River and Connection Slough sites until PG&E power is available to provide electric power to the sites. Noise emitted by the generators would attenuate to inaudible levels at the marina to the south of the Old River site. There are no noise-sensitive land uses near the Connection Slough site; therefore, noise emitted by Project generators would not adversely affect noise-sensitive receptors.

A substantial temporary or periodic increase in ambient noise levels in the project vicinity above levels existing without the project

3 **Less than Significant**. Refer to (a) above.

For a project located within an airport land use plan or, where such a plan has not been
adopted, within two miles of a public airport or public use airport, would the project expose
people residing or working in the project area to excessive noise levels

No Impact. The Project sites are not located within an airport land use plan or within 2 miles of
a public airport.

9 f. For a project within the vicinity of a private air strip, would the project expose people residing 10 or working in the project area to excessive noise levels

11 **No Impact**. The Project sites are not located within the vicinity of a private air strip.

12 **4.12.3.3 Cumulative Impacts**

Noise impacts are highly localized. No other Projects would be located in the same general
location as the 2-Gates Project, and no cumulative impacts would occur.

15

16